

# Requeue Request Manual

1.0.0

---

## Data

Section: 1.1

Name:	data
Full Path:	requeueRequest.data
Type:	String Value
Is Required?:	Yes
Minimum Length:	
Maximum Length:	
JSON Reference Data:	<a href="https://borderconnect.com/data/data-types.json">https://borderconnect.com/data/data-types.json</a>

### Sample JSON:

```
"data": "REQUEUE_REQUEST"
```

### Description:

- Specifies type of message. For requeue request must be exactly "REQUEUE\_REQUEST"

---

## From Date and Time

Section: 1.2

Name:	fromDateTime
Full Path:	requeueRequest.fromDateTime
Type:	String Value
Is Required?:	No
Minimum Length:	19
Maximum Length:	19

### Sample JSON:

```
"fromDateTime": "2016-01-05 04:00:00"
```

### Description:

- Date and time at beginning of range of messages to be requeued.
- Must be in format yyyy-mm-dd hh:mm:ss
- If fromDateTime is present, toDateTime must also be present.

---

## To Date Time

Section: 1.3

Name:	toDateTime
Full Path:	requeueRequest.toDateime
Type:	String Value
Is Required?:	No
Minimum Length:	19
Maximum Length:	19

### Sample JSON:

```
"toDateime": "2016-01-05 04:30:00"
```

### Description:

- Date and time at end of range of messages to be requeued.
- Must be in format yyyy-mm-dd hh:mm:ss
- If toDateime is present, fromDateime must also be present.

---

## Trip Number

Section: 1.4

Name:	tripNumber
Full Path:	requeueRequest.tripNumber
Type:	String Value
Is Required?:	No
Minimum Length:	8
Maximum Length:	25

### Sample JSON:

```
"tripNumber": "12345677"
```

### Description:

- Trip number (ACE or ACI) that messages to be requeued pertain to.

---

## Message Contains

Section: 1.5

Name:	messageContains
Full Path:	requeueRequest.messageContains
Type:	String Value
Is Required?:	No
Minimum Length:	
Maximum Length:	

### Sample JSON:

```
"messageContains": "HIGHWAY"
```

### Description:

- Text that messages to be requeued must contain.

---

## Send Id

Section: 1.6

Name:	sendId
Full Path:	requeueRequest.sendId
Type:	String Value
Is Required?:	No
Minimum Length:	1
Maximum Length:	68

### Sample JSON:

```
"sendId": "001"
```

### Description:

- Unique ID assigned by the software integrating with BorderConnect.
- Will be quoted in server responses related to your JSON upload.
- e.g. if this is an ACE Trip Create operation, the server response advising the success or failure of the create will quote the value you provide in this field.
- This field is never required, nor will any validation prevent you from duplicating send IDs.